



NOTES

- ANCHOR ASSEMBLY SHALL BE USED AT EACH FREE END OF TYPE 5 GUARD OR BARRIER RAIL.
- FORM TOP 4" OF ANCHOR AND SLOPE THE TOP TO CONFORM TO SLOPE OF THE ADJACENT GROUND. THE 36" DIA. ANCHOR MAY BE REPLACED BY A 2' - 6" SQUARE ANCHOR AT THE CONTRACTORS OPTION.
- SPACERS FOR POSTS B AND C SHALL BE MADE OF 3/16" STEEL PLATE OR TWO SECTIONS OF W6x8.5 OR W8x10 CUT IN THE WEB (SEE DASHED LINE) AND WELDED TOGETHER ON BOTH SIDES.
- ALL STEEL SPACERS AND POSTS MAY BE PROVIDED WITH ADDITIONAL BOLT HOLES SO THAT THESE ITEMS WILL NOT BE REQUIRED TO BE MADE RIGHT AND LEFT HANDED.
- SPACER SHALL BE FASTENED TO THEIR POSTS WITH TWO 5/8" HEXHEAD BOLTS AND NUTS WITH STANDARD WASHERS ON BOTH SIDES.
- PLACE ONE RECTANGULAR WASHER BETWEEN POST BOLT HEAD OR NUT AND THE FACE OF RAIL.
- ALL OTHER WASHERS INDICATED ON THIS DRAWING ARE STANDARD GALVANIZED STEEL OF THE APPROPRIATE SIZE.
- CONCRETE: ALL CONCRETE SHALL BE CLASS "A".
- MINIMUM POST ENCASEMENT SHALL BE 4".